



Kumho CVT FLUID

New generation high-performance Transmission and Gear oil

Definition

KUMHO CVT FLUID is transmission oil suitable for CVT type automatic transmissions operating with belt and chain drive method.

Places of Use

• Audi Multitronic • BMW Mini Cooper EZL 799A/ 83 22 0 136 376/ 83 22 0 429 154 • Chery CVT • Daihatsu AMMIX CVTF DFE, CVT Fluid DC, CVT Fluid DFC, Fluid TC • Dodge/Jeep/Chrysler NS-2 • Dodge/Chrysler/Jeep/Mopar CVT+4 • Fiat Tutela Car CVT N.G • Fujijyuuko i-CVTF FG • GM/Saturn DEX-CVT, GM 1940713 and 1940714 • Honda HMMF, HCF2, Z-1, CVT • Hyundai/Kia CVT-1 / SP III • Idemitsu CVTF-EX1 • Lexus Fluid TC, Fluid FE • Mazda JWS 3320 • MG Rover EM-CVT • Mini Cooper EZL 799/EZL 799A/ZF • Mitsubishi CVT V1, CVTF-J1, CVTF-J4 and -J4+, CVTF ECO J4, SP-III • Nissan NS-1/2/3 , N-CVT • Punch CVTF-EX1 • Renault Elf Matic CVT, CVT CK/SK/FK • Shell Green 1V • Subaru iCVT, iCVT FG, ECVT, Lineartronic chain CVT and CVT II Fluid, K0425Y0710 & K0425Y0711, Lineartronic High Torque (HT) CVT Fluid, CV-30, K0421Y0700, NS-2, iCVT FG • Suzuki CVTF TC, CVTF 3320, CVTF 4401, NS-2, CVT Green 1 & 2, CVT Green 1V • Toyota CVTF TC, CVTF FE • Volvo CVT 4959 • VW/Audi TL 521 16 (G 052 516), TL 521 80 (G 052 180 A2) • Zotye CVTs

Features and Benefits

- Shake-free driving comfort with improved friction regulator feature
- Safe driving
- Longer equipment life
- Extended service interval
- High gasket and felt compatibility

Specifications and Approvals:

Specially designed for CVTs with metal belt and metal chain in Japanese cars.

Test	Unit	Test method	Ideal values
Density, 15°C	g/liter	ASTM D 4052	0,845
Viscosity, 100°C	mm ² /s	ASTM D 445	7,64
Viscosity Index		ASTM D 2270	180
Pour Point	°C	ASTM D 97	-41
Flash Point COC	°C	ASTM D 92	230

Values shown may differ between productions.