

Kumho Nismo S 5w-30

New generation high-performance automotive oil

Definition

KUMHO Nismo S 5W-30 medium-viscosity synthetic engine oil for modern passenger car gasoline and diesel engines with direct and multi-point fuel injection, turbocharged and non-turbocharged. Developed in accordance with the requirements of Chinese car manufacturers.

Places of Use

KUMHO Nismo S 5W-30; TIt is designed for all gasoline and diesel engines in passenger cars, light SUVs, vans and light trucks, as well as SUVs and light commercial vehicles where API SP/ILSAC GF-6A/GM Dexos 1 Gen3 and lower performance levels of this viscosity grade are required.

Features and Benefits

- Provides high engine performance.
- Extends the life of exhaust emission systems.
- Protects the environment by contributing to low emissions.
- It keeps the engine clean by reducing the formation of sediment and debris.
- Helps save fuel

Specifications and Approvals:

API SP/RC, ILSAC GF-6A., GM DEXOS I:GEN 3

Test	Unit	Test method	Ideal values
Density, 15°C	g/liter	ASTM D 4052	0,85
Viscosity, 100°C	mm²/s	ASTM D 445	9,3-12,5
Viscosity Index		ASTM D 2270	164
Pour Point	°C	ASTM D 97	-35
Flash Point COC	°C	ASTM D 92	230

Values shown may differ between productions.