



## Kumho Taso 40W-50W-60W-70W

New generation high-performance Heavy Duty Diesel oil

### Definition

Are mineral based lubrication oils for general purposes, formulated with well-refined high quality base oils. They are suitable to be used in every type of automotive and industrial applications, where no heavy duty conditions present and lubrication is necessary

### Places of Use

All trucks, buses, semi-trailers, trucks with diesel engines, especially turbocharged and low-emission diesel engines Recommended for construction equipment and generator applications

### Features and Benefits

- By the help of detergent and dispersant additives, they protect the system, improve the system life and prevent performance loss
- They provide protection of the system by preventing wears that could occur as a result of high pressure,
- By preventing deposit formation, they keep the systems very clean.

### Specifications and Approvals:

API SG/CF-4/ACEA E2, Mercedes-Benz MB 228.1/29.1, MAN 271, MTU Type1, Volvo VDS, Mack EO-K/2, Deutz DQC I-02, CCMC G4/D4/ P.D. -2, MIL-L-46152EK, MIL-L-2104D, GM 6085-M, Ford M2K153K

Test	Unit	Test method	40W	50W	60W	70W
Density, 15°C	g/liter	ASTM D 4052	0,888	0,889	0,889	0,89
Viscosity, 100°C	mm <sup>2</sup> /s	ASTM D 445	14,7	19,6	25,2	33,5
Viscosity Index		ASTM D 2270	132	182	237	325
Pour Point	°C	ASTM D 97	-21	-24	-18	-21
Flash Point COC	°C	ASTM D 92	238	244	246	240

Values shown may differ between productions.