

Kumho Taso S 15w-40

New generation high-performance Heavy Duty Diesel oil

Definition

It is a long-lasting diesel engine oil at the super high performance diesel engine oil (SHPD) quality level it provides excellent performance in diesel engines running on low and high sulfur fuels

Places of Use

All trucks, buses, semi-trailers, trucks with diesel engines, especially turbocharged and lowemission diesel engines Recommended for construction equipment and generator applications

Features and Benefits

- It protects the engine in fuels with high TBN values and high sulfur content.
- It is safe in all turbocharged and non-turbocharged engines by preventing wear at high speeds and temperatures.
 provides usage.
- It increases combustion efficiency and engine power by keeping the engine clean.
- Neutralizes combustion acids even when working with high sulfur fuels.
- Provides long gasket and seal life.
- It is long lasting

Specifications and Approvals:

API CI-4/SL/SC, ACEA E7, DTFR 15B110, Volvo VDS-3, Mack EO-N, Renault VI RLD-2, Deutz DQC III-18, MTU TYPE 2.0, JASO DH- 1, Global DHD-1, Cummins CES 20077/78, Detroit Diesel DDC 93K215, MAN M3275, CAT ECF-1A

Test	Unit	Test method	Ideal values
Density, 15°C	g/liter	ASTM D 4052	0,886
Viscosity, 100°C	mm²/s	ASTM D 445	15,7
Viscosity Index		ASTM D 2270	138
Pour Point	°C	ASTM D 97	-30
Flash Point COC	°C	ASTM D 92	240

Values shown may differ between productions.